

Technical sheet :


MC 30-4 ST5



 **MANITOU**
HANDLING YOUR WORLD

	Technical characteristics		Metric
1.1	Manufacturer		Manitou
1.2	Model Name		MC 30-4 ST5
1.3	Power source		Diesel
1.4	Operator type		Seated
1.5	Max. capacity	Q	3000 kg
1.6	Load center of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	x	630 mm
1.9	Wheelbase	y	2000 mm
	Weight		
2.1	Service weight		4266 kg
2.2	Weight on front axle (laden) / rear axle (laden)		6267 kg / 999 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1582 kg / 2684 kg
	Wheels		
3.1	Tires type		Pneumatic
3.2	Dimensions of front wheels		12,5/80-18/12 SL R4
3.3	Dimensions of rear wheels		27x10-12 SKS
3.5	Number of front wheels / rear wheels		2 / 2
3.5.2	Number of drive wheels		4
3.6	Front wheel gauge	b10	1159 mm
3.7	Rear wheel gauge	b11	1176 mm
	Dimensions		
4.7	Height of overhead guard (cabin) / Overall height of low overhead guard (Buggie version)	h6	2176 mm / 2028 mm
4.8	Seat height/stand height	h7	1130 mm
4.19	Overall length	l1	4401 mm
4.20	Length to face of forks	l2	3201 mm
4.21	Overall width	b1	1450 mm
4.22	Forks section x width x length	s / e / l	45 mm x 100 mm / 1200 mm
4.23	Fork carriage ISO 2328 (class/form) A/B		3A
4.24	Fork carriage width	b3	1260 mm
4.31	Ground clearance below mast	m1	300 mm
4.32	Ground clearance at centre of wheelbase	m2	315 mm
4.33	Aisle width for 1000 x 1200 pallet widthways	Ast	5273 mm
4.35	Turning radius	Wa	3450 mm
	Performances		
5.1	Travel speed (laden / unladen)		10 km/h / 24 km/h
5.2	Lifting speed (laden / unladen)		0.39 m/s / 0.39 m/s
5.3	Lowering speed (laden / unladen)		0.50 m/s / 0.30 m/s
5.5	Drawbar pull (Laden)		3050 daN
5.7	Gradeability (laden)		47 %
5.10	Service brake		Hydraulic brakes by loss of pressure
	Transmission type		Hydrostatic
	Engine		
7.1	Engine brand / model / norm		Kubota / D1803 CRT E5 / Stage V
7.2	Engine power (kW)		37 kW
7.3	Rated speed		2800 rpm
7.4	Number of cylinders / Capacity of cylinders		3 - 1826 cm³
	Miscellaneous		
8.1	Type of drive control		Electronic
8.2	Working hydraulic pressure for attachments		220 bar
8.3	Oil flow rate for attachments		38 l/min

MC 30-4 ST5 - Dimensional drawing



Characteristics of masts and residual capacities

Full Visibility Duplex (FVD)		FVD 30	FVD 33	FVD 37	FVD 40	FVD 45
α - Mast/fork carriage tilt, forward	°	12	12	12	12	12
β - Mast/fork carriage tilt, backward	°	10	10	10	10	10
h1 - Mast lowered height	mm	2188	2338	2598	2788	3038
h2 - Mast free lift	mm	117	117	117	117	117
h3 - Mast lifting height	mm	3000	3300	3700	4000	4500
h4 - Mast extended height	mm	3790	4090	4490	4790	5290
Residual capacity at max height	kg	3000	3000	1900	1260	550
Residual capacity with hooked-on side shift at max heighth	kg	2780	2780	2000	1250	400
Height at max capacity	mm	3000	3300	3300	3300	3300
Height at max capacity with hooked-on sideshift	mm	3000	3300	3300	3300	3300

Free Lift Triplex (FLT)		FLT 34	FLT 37	FLT 40	FLT 43	FLT 47	FLT 50	FLT 55
α - Mast/fork carriage tilt, forward	°	12	12	12	12	12	12	6
β - Mast/fork carriage tilt, backward	°	10	10	10	10	10	10	6
h1 - Mast lowered height	mm	1988	2088	2188	2338	2438	2598	2788
h2 - Mast free lift	mm	1235	1335	1435	1585	1685	1845	2035
h3 - Mast lifting height	mm	3400	3700	4000	4300	4700	5000	5500
h4 - Mast extended height	mm	4236	4536	4836	5136	5536	5836	6336
Residual capacity at max height	kg	2800	1980	1300	800	380		
Residual capacity with hooked-on side shift at max heighth	kg	2780	2040	1280	710	200		
Height at max capacity	mm	3350	3350	3350	3350	3350		
Height at max capacity with hooked-on sideshift	mm	3400	3350	3350	3350	3350		

Full Visibility Triplex (FVT)		FVT 33
α - Mast/fork carriage tilt, forward	°	12
β - Mast/fork carriage tilt, backward	°	10
h1 - Mast lowered height	mm	1878
h2 - Mast free lift	mm	129
h3 - Mast lifting height	mm	3300
h4 - Mast extended height	mm	4079

Equipment

Standard
Differential Lock
Easy link
Ecostop
Enclosed cab
Front tires - Rough terrain profil
Inching Pedal
Mechanical suspension PVC seat - Grammer MSG65
Open cab
Operation Safety System (OSS)
Rear tires - Rough terrain profil
Rear working light
Switch 2WD / 4WD
Optional
Audio warning on reverse
Enclosed Cab with Heat and A/C
Front and Rear - Work Lights
Joystick Switch and Move (JSM)
LED Rotative Beacon
Load backrest
Open cab
Pneumatic seat
Sideshift carriage



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes